

Nurse Call Points



Alarm Radio Monitoring
01568 610 016

arm nurse call points are made from robust plastic embedded with anti-microbial additives to help provide a defence against the spread of infection.

Call Points are battery operated and come complete with a wall bracket for securing to the wall.

The bracket's locking tab, enables the call point to be moved or relocated easily within the room if required.

On the front of the call points there is an infra-red sensor which allows remote activation by using a staff or service user infra-red fob or pendant.



There are different variants of the **arm** nurse call point available to suit different rooms & requirements.

••• S64-NPP-IR

Call Point comes with Pear Push Call Lead and Wall Holster.

The S64-NPP-IR call point has a monitored socket to connect the Call Lead or Assistive Technology devices.



A double adapter enables the Pear Push Call Lead and another device to be plugged into the call point at the same time (e.g. Call Lead & Movement Sensor).

Assistive Technology devices available such as: Out of Bed Monitors, PIR Movement Sensors, Epilepsy Sensor, Enuresis Sensor, Pillow Switch, Pressure Mats (floor, chair, bed) plus many more.

••• S64-NPC-IR

Call Point comes with integral Pull Cord with 2 easy grip triangles.

Wireless Ceiling mounted Pull Cords are available for locating in shower areas.



••• S64-NAB-IR

Call Point comes with Air Bulb.

Floor Pressure Pads/Discs are available.



••• S64-NSC-IR

Call Point comes with Staff Call & Emergency only.

Anti-Ligature Shroud available.




••• S64-NDM-IR

Call Point comes with Door Contacts and Staff Override keyswitch to disable door monitoring when required.

Also available:
Door Bell monitor: S64-NDMB-IR
Telephone monitor: S64-NTIF



Nurse Call Points



Technical Specification:

••• Size	Height = 110 mm Width = 100 mm Depth = 40 mm (including wall bracket)
••• Weight	114 gms
••• Casing	ABS casing & buttons Casing & buttons embedded with anti-microbial additives
••• Pear Push Call Lead	2.5m standard length (longer lengths available upon request)
••• Call Types	Patient Call Staff Call Emergency Reset Staff Presence Lead Removed Low Battery Fault Door Open Door Bell
••• Infra Red Sensor	For use with Staff/Service User infra-red fobs pendants beltclips
••• Call Reassurance	Call Points incorporate a reassurance LED & tone
••• Call Escalation	Automatic escalation of calls if unanswered. (time period configurable)
••• Power	1 x 3.6v AA lithium battery
••• Battery Life	3-4 years under normal operating conditions
••• System Size	Up to 3,000 devices Factory set unique identity
••• Frequency	173.225 MHz
••• Standards	EN 301 489 EN 300 220 RoHS WEEE